



### Air Operated Pump (Tensioners)

The 10-6 series pump is a safe, low maintenance and durable unit that meets the requirements of all on-site bolt tensioning operational needs.

This air operated pump is particularly suitable for projects where a higher oil flow is required, such as subsea duties or where a large number of high capacity tensioners are being used.

**D3001A0115AA** (Approximate Rate of Discharge Litres per Minute/Cubic Inches per Minute)

Air (bar/psi)		Fluid Discharge Pressure (bar/psi)															
		0	0	207	3000	414	6000	621	9000	862	12500	1034	15000	1379	20000	1724	25000
4	60	1.00	61	0.80	49	0.70	43	0.62	38	0.51	31	0.44	27	0.00	0	0.00	0
6	80	1.07	65	0.93	57	0.84	51	0.75	46	0.66	40	0.61	37	0.49	30	0.16	10
7	100	1.15	70	0.97	59	0.88	54	0.80	49	0.72	44	0.66	40	0.56	34	0.46	28
Empty Weight		Air Consumption			Pack Dimensions												
						mm	in										
kgs	lbs	m <sup>3</sup> /min	L/min	cfm	L	380	14.96	W	400	15.75	H	438	17.24				
23.5	52	1.586	1586	56													

Further details can be obtained from your local Hydratight representative or via the website [www.hydratight.com](http://www.hydratight.com)